

➤ FIT Series Solenoid Pump



Features:

- Multifunction digital control :
Constant and proportional modes
- Construction: All wet ends are PVDF
- Automatic venting head available
- pH and Redox control
- PTFE diaphragm
- Pulse and 4-20

Model	Max GPH	ML/Stroke	Strk per min	Max PSI	Tubing
2001	.26	.09	180	290	3/8 x 1/2
1802	.53	.19	180	261	1/4 x 3/8
1804	1.06	.37	180	261	1/4 x 3/8
1502	.53	.19	180	218	1/4 x 3/8
1504	1.06	.37	180	218	1/4 x 3/8
1505	1.32	.46	180	218	1/4 x 3/8
1004	1.06	.37	180	145	1/4 x 3/8
1005	1.32	.46	180	145	1/4 x 3/8
1010	2.64	.93	180	145	1/4 x 3/8
0706	1.59	.56	180	102	1/4 x 3/8
0510	2.64	.93	180	73	1/4 x 3/8
0512	3.17	1.11	180	73	1/4 x 3/8
0408	2.11	.74	180	58	1/4 x 3/8
0310	2.64	.93	180	44	1/4 x 3/8
0215	3.96	1.39	180	29	3/8 x 1/2
0116	4.23	1.48	180	15	3/8 x 1/2